

**technical data**

process connection	G1/2" hygienic
material (process-intrusive)	316L *1
torque	metal-Peek: 5-10Nm
torque	metal-metal: 5...20Nm

ambient conditions

process pressure	max 10bar
------------------	-----------

Miscellaneous

labelling	by engraving of housing, "batch-no"
-----------	-------------------------------------

Type key configuration

Pos.:	Physical characteristics	Key	Characteristic
1	design	A0	RDxW DN25 Ø29mmx1,5mm GL 100mm HM 51,5mm
		A1	RDxW DN32 Ø35mmx1,5mm GL 110mm HM 54mm
		A2	RDxW DN40 Ø41mmx1,5mm GL 120mm HM 57mm
		A3	RDxW DN50 Ø53mmx1,5mm GL 140mm HM 63,5mm
		A4	RDxW DN65 Ø70mmx1,5mm GL 160mm HM 73,5mm

Existing configurations

Type	Order number	Item number	Old order number
PA1001	<u>PA1001-A1</u>	800-140	
PA1001	<u>PA1001-A2</u>	800-142	
PA1001	<u>PA1001-A3</u>	800-138	
PA1001	<u>PA1001-A4</u>	800-139	

Remarks

*1 in contact with product PB

Revision

Version	Effective from	Comment
<u>1.0</u>	22.07.2014 06:37:09	Typenblatt angelegt