



**TECHNICAL DATA**

measuring range	-40°C...+180°C
response time	at present not determined
material casing	1.4301
protection class	III
protection category	IP67 according to DIN EN 60529
tensile strain (cable to sleeve)	max 20N
connection wire (cable-jacket/wire)	silicone/silicone 180°C, 4x0,35mm <sup>2</sup> , CuSn
colour of cable	black/anthracite
testing voltage	500V *1

**AMBIENT CONDITIONS**

dew-point-resistance	no
storage temperature	+5°C...+70°C
process pressure	at normal pressure

**MISCELLANEOUS**

labelling	by labelling on cable "order-no +WW/YY"
-----------	---

**TYPE KEY CONFIGURATION**

Pos.:	Physical characteristics	Key	Characteristic
1	sensorelement-type	A0	Pt100, tolerance class B according to DIN EN 60751
		A1	Pt100, tolerance class A according to DIN EN 60751
		A2	Pt1000, tolerance class B according to DIN EN 60751
		A3	Pt1000, tolerance class A according to DIN EN 60751
2	cable length KL	B0	2000mm-50+100 *2
		B1	5000mm -100+200 *2
3	sensor connection	C0	wire end sleeves orange 0,5mm <sup>2</sup>
		C1	wire ends tinned

**EXISTING CONFIGURATIONS**

Type	Order number	Item number	Old order number
TF6x6-1001	<u>TF6x6-1001-A0B0C0</u>	800-874	

**REMARKS**

\*1 measured in water 70°C, 0,04m/sec

\*2 stripping length AL=40mm +10-10

We reserve the right to make technical modifications and correction at any time without prior notice!

This version of the data / type sheet is a translation by a partner. We assume no liability for translation errors. If the translation contains errors or ambiguities, the German version of the data / type sheet is to be used.

**REVISION**

Version	Effective from	Comment
---------	----------------	---------

