



**TECHNICAL DATA**

measuring range	-25°C...+90°C /UL: max 80°C
response time	at present not determined
material casing	1.4301
protection class	III
protection category	IP54 according to DIN EN 60529
tensile strain (cable to sleeve)	max 10N
connection wire (cable-jacket/wire)	PUR(TPU) /PP 4x0,34mm <sup>2</sup> *1
insulation resistance	500V
colour of cable	black/anthracite

**AMBIENT CONDITIONS**

application area	dry use
dew-point-resistance	no
storage temperature	+5°C...+70°C
process pressure	at normal pressure

**MISCELLANEOUS**

labelling	by labelling on cable "order-no +WW/YY"
-----------	---

**TYPE KEY CONFIGURATION**

Pos.:	Physical characteristics	Key	Characteristic
1	sensorelement-type	A0	Pt100, tolerance class B according to DIN EN 60751
		A1	Pt100, tolerance class A according to DIN EN 60751
		A2	Pt100, tolerance class AA according to DIN EN 60751
		A3	Pt1000, tolerance class B according to DIN EN 60751
		A4	Pt1000, tolerance class A according to DIN EN 60751
		A5	Pt1000, tolerance class AA according to DIN EN 60751
		A6	NTC 10K@25°C B25/85=3977 B±1%/R±1% *2
2	cable length KL	B0	2000mm-50+100 *3
		B1	5000mm -100+200 *3
3	sensor connection	C0	wire end sleeves grey 0,75mm <sup>2</sup>

**EXISTING CONFIGURATIONS**

Type	Order number	Item number	Old order number
TF6x6-1004	<u>TF6x6-1004-A3B0C0</u>	800-884	

**REMARKS**

\*1 S-PUR MOTION cULus AWM STYLE 20549 AWM I/II A/B 80C 300V FT2

\*2 !!! CAUTION: This sensor element can only be loaded up to 125°C (short-term 150°C). The maximum temperature of the sensor is affected by this restriction!!!

\*3 stripping length AL=40mm +10-10

We reserve the right to make technical modifications and correction at any time without prior notice!

This version of the data / type sheet is a translation by a partner. We assume no liability for translation errors. If the translation contains errors or ambiguities, the German version of the data / type sheet is to be used.

**REVISION**

Version	Effective from	Comment
<u>1.0</u>	10.12.2014 08:56:11	Typenblatt angelegt