



technical data

measuring range	-40°C...+130°C (kurzfristig 150°C)
process connection	M10
response time	T05=2sec/T09=5sec *1
minimum immersion depth	27mm
material (process-intrusive)	1.4435/ 1.4404/ 1.4571
Material Überwurfmutter	CuZn39Pb3
protection category	IP54 gemäß DIN EN 60529
insulation resistance	500V
connection wire (cable-jacket/wire)	PFA/ PFA , 250°C, 4xAWG26, CuNi
across flats	SW12
colour of cable	white

ambient conditions

dew-point-resistance	no
----------------------	----

Miscellaneous

labelling	by labelling on cable "order-no +WW/YY"
-----------	---

Type key configuration

Pos.:	Physical characteristics	Key	Characteristic
1	installation length "EL"	A0	27mm
		A1	50mm
2	sensorelement-type	B0	Pt100, tolerance class A according to DIN EN 60751
		B1	Pt100, tolerance class AA according to DIN EN 60751
		B2	Pt1000, tolerance class A according to DIN EN 60751
		B3	Pt1000, tolerance class AA according to DIN EN 60751
3	cable length KL	C0	2500mm-50+100 *2
		C1	5000mm -100+200 *2
4	sensor connection	D0	wire end sleeves blue 0,25mm ²

Existing configurations

Type	Order number	Item number	Old order number
------	--------------	-------------	------------------

Remarks

*1 measured in water 70°C, 0,04m/sec

*2 stripping length AL=40mm +10-10

We reserve the right to make technical modifications and correction at any time without prior notice!

This version of the data / type sheet is a translation by a partner. We assume no liability for translation errors. If the translation contains errors or ambiguities, the German version of the data / type sheet is to be used.

Revision

Version	Effective from	Comment
1.0	05.02.2015 14:17:40	Typenblatt angelegt