



TECHNICAL DATA

measuring range	-50°C...+180°C
process connection	G1/8"
response time	at present not determined
material (process-intrusive)	1.4401/1.4404/ 1.4571 (316/316L/316Ti)
protection category	IP67 according to DIN EN 60529
insulation resistance	500V
connection wire (cable-jacket/wire)	silicone/silicone 180°C,4x0,35mm ² , CuSn
across flats	AF13
colour of cable	black/anthracite

AMBIENT CONDITIONS

operating temperature	-30°C...180°C
dew-point-resistance	no

MISCELLANEOUS

labelling	by labelling on cable "order-no +WW/YY"
-----------	---

TYPE KEY CONFIGURATION

Pos.:	Physical characteristics	Key	Characteristic
1	installation length "EL"	A0	25mm
2	sensorelement-type	B0	Pt100, tolerance class B according to DIN EN 60751
		B1	Pt100, tolerance class A according to DIN EN 60751
		B2	Pt1000, tolerance class B according to DIN EN 60751
		B3	Pt1000, tolerance class A according to DIN EN 60751
		B4	NTC 10K@25°C B25/85=3977 B±1%/R±1%, valid from 50°C, <50°C is B2%/R2% *1
3	cable length KL	C0	2000mm-50+100 *2
		C1	5000mm -100+200 *2
4	sensor connection	D0	wire end sleeves orange 0,5mm ²
		D1	wire end sleeves grey 0,75mm ²

EXISTING CONFIGURATIONS

Type	Order number	Item number	Old order number
TP1126	TP1126-A0B1C0D0	800-872	

REMARKS

*1 NTC glas encapsulated, T_{max}=250°C
 *2 stripping length AL=40mm +10-10

We reserve the right to make technical modifications and correction at any time without prior notice!

This version of the data / type sheet is a translation by a partner. We assume no liability for translation errors. If the translation contains errors or ambiguities, the German version of the data / type sheet is to be used.

REVISION

Version	Effective from	Comment
<u>1.0</u>	27.02.2017 10:20:30	Typenblatt angelegt