



TECHNICAL DATA

measuring range	-40°C...+180°C
response time	T05=5sec/ T09=15sec *1
material (process-intrusive)	1.4404/1.4571 (316L/316Ti)
outer diameter tube D	4mm
protection category	IP67 according to DIN EN 60529
protection class	III
tensile strain (cable to sleeve)	max 20N
connection wire (cable-jacket/wire)	silicone/ PTFE 4xAWG26/7
insulation resistance	750V DC Prüfspannung *1
colour of cable	grey

AMBIENT CONDITIONS

application area	liquid and gaseous media
dew-point-resistance	no
storage temperature	-20°C...+70°C
process pressure	at normal pressure

MISCELLANEOUS

labelling	by engraving on sleeve, "batch-no+WW/YY"
-----------	--

TYPE KEY CONFIGURATION

Pos.:	Physical characteristics	Key	Characteristic
1	length of sleeve HL	A0	40mm
		A1	100mm
2	sensorelement-type	B0	Pt100, tolerance class A according to DIN EN 60751
		B1	Pt100, tolerance class AA according to DIN EN 60751
		B2	Pt1000, tolerance class A according to DIN EN 60751
		B3	Pt1000, tolerance class AA according to DIN EN 60751
3	cable length KL	C0	2000mm-50+100 *2
		C1	5000mm -100+200 *2
4	sensor connection	D0	wire end sleeves 0,25mm ²

EXISTING CONFIGURATIONS

Type	Order number	Item number	Old order number
------	--------------	-------------	------------------

REMARKS

measured in water 70°C, 0,04m/sec
 *1 measured in water 70°C, 0,04m/sec

*2 stripping length AL=40mm +10-10

We reserve the right to make technical modifications and correction at any time without prior notice!

This version of the data / type sheet is a translation by a partner. We assume no liability for translation errors. If the translation contains errors or ambiguities, the German version of the data / type sheet is to be used.

REVISION

Version	Effective from	Comment
<u>1.0</u>	02.06.2017 13:19:10	Typenblatt angelegt