



TECHNICAL DATA

measuring range	-40°C...150°C
response time	T05=9sec/ T09=23sec *1
material (process-intrusive)	PTFE/PFA *1
outer diameter tube D	4mm
protection category	IP69K, IP68 according to DIN EN 60529
protection class	III
tensile strain (cable to sleeve)	max 10N
connection wire (cable-jacket/wire)	PFA/ PFA , 250°C, 4xAWG26, CuAg *1
insulation resistance	750V DC Prüfspannung *1
colour of cable	white

AMBIENT CONDITIONS

application area	liquid and gaseous media
application in water steam	yes, for autoclave up to xx°C, max pressure xxbar
storage temperature	+5°C...+70°C

MISCELLANEOUS

labelling	by labelling on cable "order-no +WW/YY"
-----------	---

TYPE KEY CONFIGURATION

Pos.:	Physical characteristics	Key	Characteristic
1	length of sleeve HL	A0	40mm
		A1	100mm
2	sensorelement-type	B0	Pt100, tolerance class B according to DIN EN 60751
		B1	Pt100, tolerance class A according to DIN EN 60751
		B2	Pt1000, tolerance class B according to DIN EN 60751
		B3	Pt1000, tolerance class A according to DIN EN 60751
3	cable length KL	C0	2000mm-50+100 *2
		C1	5000mm -100+200 *2
4	sensor connection	D0	wire end sleeves 0,14mm ²

EXISTING CONFIGURATIONS

Type	Order number	Item number	Old order number
------	--------------	-------------	------------------

REMARKS

measured in water 70°C, 0,04m/sec
 *1 measured in water 70°C, 0,04m/sec

*2 stripping length AL=40mm +10-10

We reserve the right to make technical modifications and correction at any time without prior notice!
 This version of the data / type sheet is a translation by a partner. We assume no liability for translation errors. If the translation contains errors or ambiguities, the

German version of the data / type sheet is to be used.

REVISION

Version	Effective from	Comment
<u>1.0</u>	10.07.2017 15:58:13	Typenblatt angelegt